


African Pegmatite (Pty) Ltd
27 Van Der Bijl Street,
PO Box 598, Meyerton 1960
Gauteng, South Africa
Email: wenger@pegmatite.co.za
reception@pegmatite.co.za
Website: www.mineralmilling.com

Tel: +27 016 362 0600/1/2/3/4
Int: +27 16 362 0600
Fax: 016 362 1239

MILLERS & PROCESSORS OF BASE MINERALS



Approved By: EJ Wenger
Compiled By: G Wagner

Doc No. : DS 005
Rev No. : 03

Date: 27 January 2012
Page 1 of 1

Data Sheet



Product: Brown Oxide
Grades: Standard

CHEMICAL ANALYSIS %

	Spec	
Mn	48.0 – 49.0 %	Moisture 1%
SiO ₂	5.0 – 7.0 %	
Fe	11.0 – 13.0 %	
CaO	4.60 – 7%	
MgO	0.44 – 3%	

PHYSICAL PROPERTIES:

Fineness	+75µm	10%max
----------	-------	--------

APPLICATION:

Used as a colourant in ceramics, glass, brick and the tile industries. Soil nutrient. Cost effective pigment putties, cement and paints.

PACKING:

Packed in 3ply 40kg paper bags, stretch-wrapped on pallets.

The information and recommendations in this product data sheet are based on data we believe to be reliable. They are offered in good faith, but do not imply any warranty or performance guarantee, as conditions and methods of use of our products are beyond our control. As such, African Pegmatite Company South Africa makes no express or implied warranties of any kind with respect to this product, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.

We recommend that the user determine whether the products and the information given are appropriate, and that the suitability and performance of our products are appropriate by testing with its own equipment. Specifications are subject to change without notice.

The information and recommendations given in this product data sheet should not be understood as a recommendation for the use of our products in violation of any patent or as a license to use any patents of the African Pegmatite Company South Africa.

Tel: +27 16 362-0600/4 Fax: +27 16 362-1239 Website: www.mineralmilling.com

